



IP遠端電源監控系統



型號: JL-8B-15Z

- ◎ 透過網路控制遠端設備電源開關，代替人員親臨現場。
- ◎ LED 面板數位電錶可查看耗電量(總電流)及IP等資料。
- ◎ 具有超載斷路保護器，防止電路超載，損壞設備。
- ◎ 可外接溫溼度偵測器，防止電路超載，設備損壞。
- ◎ 支援電源順序啟動設定，防止全部開關同時啟動，造成瞬間超載影響設備運作。
- ◎ 提供多組可自行設定的帳號與密碼，管理不同的電源開關。
- ◎ 可預約開關機時間即安排電源工作行程。
- ◎ 簡訊、電子郵件警告，實現對重要設備即時監測及警告。
- ◎ 紀錄使用者操作訊息及操作異常訊息，供使用者日後查詢。
- ◎ 支援SNMP(V1/V2/V3)協議、SNMP Trap。
- ◎ 支援Web API (JSON格式控制) 及SNMP控制、管理者可自行開發種軟體。
- ◎ 提供遠端網路線上韌體更新功能。

IP remote control power management

JL-8B-15Z

User: admin Login Time: 03/18 15:11 Will be logout after 28:49

[Reset](#)

[Logout](#)

MONITOR

SYSTEM

FIREWALL

ACCOUNT

TIME

CHART

EVENT

UPGRADE

0 0 0

Infeed

Outlet

Temperature

RH Sensor

No	Name	PC	Switch	All	Control Action
1	Port 1		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup
2	Port 2		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup
3	Port 3		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup
4	Port 4		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup
5	Port 5		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup
6	Port 6		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup
7	Port 7		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup
8	Port 8		<input type="checkbox"/> ON	<input type="checkbox"/>	Setup

IP remote control power management

JL-8B-15Z

User: admin Login Time: 03/18 15:11 Will be logout after 27:48

[Reset](#)

[Logout](#)

MONITOR

SYSTEM

FIREWALL

ACCOUNT

TIME

CHART

EVENT

UPGRADE

0 0 0

Infeed

Outlet

Temperature

RH Sensor

Device Temp: 47.1°C

[Setup](#)

External Port	Name	Off-line Monitor	Status	Temp	All
1	Port 1	<input type="checkbox"/>		0 °C	Setup
2	Port 2	<input type="checkbox"/>		0 °C	Setup
3	Port 3	<input type="checkbox"/>		0 °C	Setup
4	Port 4	<input type="checkbox"/>		0 °C	Setup
5	Port 5	<input type="checkbox"/>		0 °C	Setup
6	Port 6	<input type="checkbox"/>		0 °C	Setup
7	Port 7	<input type="checkbox"/>		0 °C	Setup

IP remote control power management

JL-8B-15Z

User: admin Login Time: 03/18 15:11 Will be logout after 29:51

Reset

Logout

MONITOR

SYSTEM

FIREWALL

ACCOUNT

TIME

CHART

EVENT

UPGRADE

Network

Email Server

SMS Server

SNMP

Syslog

IDCView

Serial Port

Peripheral

Other

Host Settings

Ping Test

Enabled DHCP:

Host: 192.168.55.23

Subnet Mask: 255.255.255.0

Gateway: 192.168.55.1

Ethernet Card Speed: Auto Negotiation

MAC: 00:1F:36:00:03:05

Domain Name Server

Primary DNS Server: 8.8.8.8

Secondary DNS Server:

Web Server

Enabled HTTP:

Enabled HTTPS:

Http Port: 80

Https Port: 443

Firewall

Disable ICMP echo (ping) responses:

Save

IP remote control power management

JL-8B-15Z

User: admin Login Time: 03/18 15:11 Will be logout after 29:54

Reset

Logout

MONITOR

SYSTEM

FIREWALL

ACCOUNT

TIME

CHART

EVENT

UPGRADE

Device Time

Date (YYYY/MM/DD): 2020/03/18

Time (HH:MM:SS): 15:15:50

Time Synchronization

Sync with computer

Date (YYYY/MM/DD): 2020/03/18

Time (HH:MM:SS): 15:36:27

Time Synchronization

Time Server Setting

Synchronize with Time Server

Time Server:

Time Server List

Time Zone

Time Zone: GMT + 08 : 00

Enable daylight saving time

Daylight saving time start at: January 1st Sunday 00

Daylight saving time finish at: January 1st Sunday 00

Save

產品規格	ZDL(W) 8 埠 系列	產品規格	ZDL(W) 8 埠 系列
電源插座	ZDL(W) -8A (IEC320 C13) ZDL(W) -8B (NEMA5-15R)	操作溫度	0 - 60℃
最大總輸出電流	15A / ZDL(W) -8B -15Z	操作濕度	0 - 90%
	16A / ZDL(W) -8B -16Z	儲存溫度	-25 - 65℃ (-13 - 149°F)
	20A / ZDL(W) -8B -20F	機架型式	19吋標準機架
	30A / ZDL(W) -8B -30I	外型尺寸	445 x 155 x 44 mm (W x D x H)
	32A / ZDL(W) -8B -32L	機身淨重	2.5 KG
電源輸入	100V-120V / ZDL(W) -8B	消耗功率	10W
	100V-240V / ZDL(W) -8A 47 - 63 HZ	插座數	8
電源頻率	50 - 60 HZ		

